

**Safety Data Sheet**

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

M-Print Wash

Product group:	Endprodukt
CAS No:	67-63-0
Index No:	603-117-00-0
EC No:	200-661-7
UFI:	RHH2-0JNX-8A27-345C

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Processing aid

1.3. Details of the supplier of the safety data sheet

Company name:	Merz Dental GmbH	
Street:	Kieferweg 1	
Place:	D-24321 Luetjenburg (GERMANY)	
Telephone:	+49-(0)4381-403-0	Telefax: +49-(0)4381-403-100
E-mail:	info@merz-dental.de	
Contact person:	Dipl. Chem Dr. Thomas Panther	Telephone: +49-(0)4381-403-448
E-mail:	Thomas.Panther@merz-dental.de	
Internet:	www.merz-dental.de	
Responsible Department:	Qualitaetssicherung (Quality Assurance)	

1.4. Emergency telephone

+49-(0)551-19240 (Giftinformationszentrum-Nord)

number:**Further Information**

Keep out of reach of children.

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Signal word:** Danger**Pictograms:****Hazard statements**

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P233	Keep container tightly closed.
------	--------------------------------

**Safety Data Sheet**

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 2 of 9

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.1. Substances****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			50 - < 100 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	50 - < 100 %
	inhalation: LC50 = 46,5 mg/l (vapours); dermal: LD50 = 12800 mg/kg; oral: LD50 = 5045 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

Change contaminated clothing.

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

Wash with plenty of water. After cleaning apply high-fat content skin care cream.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness. Headache. vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

**Safety Data Sheet**

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 3 of 9

5.1. Extinguishing media**Suitable extinguishing media**

Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

In use may form flammable/explosive vapour-air mixture. Vapours are heavier than air and will spread at floor level. May be released in case of fire: carbon dioxide, organic products of decomposition.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not breathe gas/fumes/vapour/spray. Provide adequate ventilation. Wear suitable gloves and eye/face protection.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs. none Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking.

Safety Data Sheet

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 4 of 9

7.3. Specific end use(s)

Solvent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day

PNEC values

CAS No	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Freshwater		140,9 mg/l
Marine water		140,9 mg/l
Soil		28 mg/kg

8.2. Exposure controls



Appropriate engineering controls

Ensure adequate ventilation of the storage area.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

**Safety Data Sheet**

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 5 of 9

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	characteristic	
		Test method
Melting point/freezing point:	-89 °C	
Boiling point or initial boiling point and boiling range:	82 °C	
Lower explosion limits:	2 vol. %	
Upper explosion limits:	13,4 vol. %	
Flash point:	12 °C	
Auto-ignition temperature:	425 °C	ASTM D 1929
pH-Value:	neutral	
Water solubility:	easily soluble	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	0,05	
Vapour pressure:	43 hPa	
(at 20 °C)		
Vapour pressure:	229 hPa	
(at 50 °C)		
Density:	0,7855 g/cm ³	
Relative vapour density:	not determined	

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Vapours may form explosive mixtures with air.

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate: not determined

Viscosity / dynamic:
(at 25 °C) 2,1 mPa·s

Flow time: not determined

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reactions with: Strong acid & Oxidizing agents.

Safety Data Sheet

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 6 of 9

10.4. Conditions to avoid

This material is combustible and can be ignited by heat, sparks, flames, or other sources of ignition (e.g. static electricity, pilot lights, or mechanical/electrical equipment). Do not spray on an open flame or other ignition source.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

May be released in case of fire: carbon dioxide, organic products of decomposition.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	5045	Rat	RTECS
	dermal	LD50 mg/kg	12800	Rabbit	RTECS
	inhalation (4 h) vapour	LC50	46,5 mg/l		

Additional information on tests

Classification according to Regulation (EC) No 1272/2008 [CLP]: Health hazard properties

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	1400	96 h Lepomis macrochirus (Bluegill)	ECOTOX Database	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	OECD-Prüfrichtlinie 301 E	95 %	21		
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	0,05

Safety Data Sheet

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 7 of 9

12.4. Mobility in soil

Mobility in soil

12.5. Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This substance does not have endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 1219
<u>14.2. UN proper shipping name:</u>	ISOPROPANOL (ISOPROPYL ALCOHOL)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3



Classification code:	F1
Special Provisions:	601
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 1219
<u>14.2. UN proper shipping name:</u>	ISOPROPANOL (ISOPROPYL ALCOHOL)
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II

Safety Data Sheet

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 8 of 9

Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A180
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

**Safety Data Sheet**

according to UK REACH Regulation

M-Print Wash

Revision date: 17.09.2024

Product code: D769

Page 9 of 9

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2010/75/EU on industrial emissions: 100 %

Directive 2004/42/EC on VOC in paints and varnishes: 100 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment is not required.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1.

Abbreviations and acronyms

Flam. Liq: Flammable liquids

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Source

ECHA Dossier

GESTIS

SDB Manufacturer