

Safety Data Sheet

according to UK REACH Regulation

Revision date: 13.07.2023

artDentine PLUS Liquid LT

Product code: artConceptPLUSLT

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

artDentine PLUS Liquid LT

UFI: JKUA-RX2S-EWMW-P331

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

The product is intended for professional use.
Material for the manufacture of dental laboratory products.

1.3. Details of the supplier of the safety data sheet

Company name:	Merz Dental GmbH	
Street:	Kieferweg 1	
Place:	D-24321 Luetjenburg (GERMANY)	
Telephone:	+49-(0)4381-403-0	Telefax: +49-(0)4381-403-100
e-mail:	info@merz-dental.de	
Contact person:	Dipl. Chem Dr. Thomas Panther	Telephone: +49-(0)4381-403-448
e-mail:	Thomas.Panther@merz-dental.de	
Internet:	www.merz-dental.de	
Responsible Department:	Qualitaetssicherung (Quality Assurance)	

1.4. Emergency telephone

+49-(0)551-19240 (Giftinformationszentrum-Nord)

number:

Further Information

none

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Skin Irrit. 2; H315
Skin Sens. 1; H317
STOT SE 3; H335

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
1,4-butanediol dimethacrylate, Tetramethylene dimethacrylate
Ethylenglicoldimethacrylat (Ethandiol-1,2-dimethacrylat)

Signal word: Danger

Pictograms:



Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 2 of 13

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Additional advice on labelling

Exemption from Article 17 [(Article 29 (2))]: Labeling of packagings with a content of <125 ml: indication of the hazard-determining components, signal word, pictograms, H317, P261, P302+P350, P333+P313.

2.3. Other hazards

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Acrylate Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
80-62-6	methyl methacrylate			50 - < 100 %
	201-297-1	607-035-00-6	01-2119452498-28	
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3; H225 H315 H317 H335			
2082-81-7	1,4-butanediol dimethacrylate, Tetramethylene dimethacrylate			5 - < 50 %
	218-218-1			
	Skin Sens. 1B; H317			
97-90-5	ethylene dimethacrylate			0.1 - < 1 %
	202-617-2	607-114-00-5		
	Skin Sens. 1, STOT SE 3; H317 H335			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
80-62-6	201-297-1	methyl methacrylate	50 - < 100 %
		inhalation: LC50 = 29,8 mg/l (vapours); dermal: LD50 = > 5000 mg/kg; oral: LD50 = 7872 mg/kg	
2082-81-7	218-218-1	1,4-butanediol dimethacrylate, Tetramethylene dimethacrylate	5 - < 50 %
		dermal: LD50 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg	
97-90-5	202-617-2	ethylene dimethacrylate	0.1 - < 1 %
		oral: LD50 = 8700 mg/kg STOT SE 3; H335: >= 10 - 100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 3 of 13

After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Rinse immediately carefully and thoroughly with eye-bath or water. If eye irritation persists: Get medical advice/attention.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink 1 glass of water. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin and eye irritation. Dizziness, Headache, Skin sensitisation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. When in doubt or if symptoms are observed, get medical advice.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air. May be released in case of fire: carbon dioxide, organic products of decomposition.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment.
Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

**Safety Data Sheet**

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 4 of 13

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Keep container tightly closed. Provide adequate ventilation as well as local exhaust at critical locations.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme.

Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Further information on handling

Put lids on containers immediately after use. Always close containers tightly after the removal of product. Keep cool. Protect from sunlight.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in a cool dry place. Protect from sunlight.

Hints on joint storage

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

Can polymerise exothermically in the absence of stabilisers, particularly in acid conditions or if shelf life exceeded. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

7.3. Specific end use(s)

Observe instructions for use.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
80-62-6	methyl methacrylate			
Worker DNEL, long-term		inhalation	local	210 mg/m³
Worker DNEL, long-term		dermal	systemic	13,67 mg/kg bw/day

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 5 of 13

PNEC values

CAS No	Substance	
Environmental compartment		Value
80-62-6	methyl methacrylate	
Freshwater		< 0,94 mg/l
Marine water		< 0,94 mg/l
Soil		-----
Air		-----

Additional advice on limit values

DNEL-/PNEC-values

Critical component: / Exposure route: / DNEL worker:

Methyl methacrylate	Long-term – inhalation, local effects 210mg/m ³
	Long-term – inhalation, systemic effects 210mg/m ³
Methyl methacrylate	Long-term - dermal, local effects 13,67 mg/kg/d
	Long-term - dermal, systemic effects 13,67 mg/kg/d
Methyl methacrylate	Long-term - oral, systemic effects -
Methyl methacrylate	PNEC Water Long-term (repeated) < 0,94 mg/l
Methyl methacrylate	PNEC Soil Long-term (repeated) -
Methyl methacrylate	air Long-term (repeated) -

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

For exposure monitoring, the following may be used: direct-reading Photo Ionisation Detector Dosimeters (e.g. ToxiRAE made by Ansyc), short-term measuring tubes for methyl acrylate (e.g. made by Dräger) or pumps with adsorption tubes, and subsequent GC analysis by an accredited institute.

Measuring method: - OSHA 94 - NIOSH 2537 - DIN EN 482 - DIN EN 689

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear safety working clothes (lab coat) and closed shoes. .

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Use only respiratory protection equipment with CE-symbol including four digit test number. Short-term filter machine, gas filter A (identification colour: brown). Only use filter machines when the surrounding atmosphere contains at least 17% vol. oxygen. Only use filter machines when the surrounding atmosphere contains at least 17% vol. oxygen.

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

**Safety Data Sheet**

according to UK REACH Regulation

Revision date: 13.07.2023

artDentine PLUS Liquid LT

Product code: artConceptPLUSLT

Page 6 of 13

Environmental exposure controls

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	ester-like	
Melting point/freezing point:	not determined	Test method
Boiling point or initial boiling point and boiling range:	100,36 °C	
Flammability:		not determined
Lower explosion limits:	2,1 vol. %	
Upper explosion limits:	12,5 vol. %	
Flash point:	10 °C	DIN 51755
Auto-ignition temperature:	290 °C	DIN 51794
Decomposition temperature:	not determined	
pH-Value:	not applicable	
Viscosity / kinematic: (at 20 °C)	~ 6 mm ² /s	
Water solubility: (at 20 °C)	~ 15 g/L	
Solubility in other solvents miscible with most organic solvents		
Vapour pressure: (at 20 °C)	38,7 hPa	
Density (at 20 °C):	0,95 g/cm ³	
Bulk density:	not applicable	
Relative vapour density: (at 20 °C)	> 1	

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The accumulation in lowlying or closed rooms can cause increased danger of fire and explosion.

Sustaining combustion:

No data available

Self-ignition temperature

Solid:

not applicable

Gas:

not applicable

Oxidizing properties

Not oxidising.

Other safety characteristics**Evaporation rate:**

not determined

Solvent separation test:

not determined

Sublimation point:

not applicable

Softening point:

not applicable

Viscosity / dynamic:

~ 0,6 mPa·s Brookfield

(at 20 °C)

SECTION 10: Stability and reactivity

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 7 of 13

10.1. Reactivity

Highly flammable. No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

May cause decomposition by long-term light influence. Stabiliser can lose its effectiveness if stored over a long period of time. The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Polymerization with heat evolution may occur in the presence of radical forming substances (e.g. peroxides), reducing substances, and/or heavy metal ions. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Heat (> 30 °C) or UV light should be avoided in order to prevent a spontaneous and explosive polymerisation and also to prevent the accompanying generation of heat.

10.5. Incompatible materials

Radical former
Reducing agent
Heavy metals
Peroxides
Oxidising agent

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicokinetics, metabolism and distribution

Methyl methacrylate is rapidly metabolized. Data apply to the main component.

Acute toxicity

Based on available data, the classification criteria are not met.

Conclusive data but not sufficient for classification

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
80-62-6	methyl methacrylate				
	oral	LD50 7872 mg/kg	Rat	RTECS	
	dermal	LD50 > 5000 mg/kg	Rabbit	REACH Dossier	OECD 402
	inhalation (4 h) vapour	LC50 29,8 mg/l	Rat	REACH Dossier	standard acute metho
2082-81-7	1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate				
	oral	LD50 10066 mg/kg	Rat	REACH Dossier	OECD 401
	dermal	LD50 > 3000 mg/kg	Rabbit	REACH Dossier	not specified
97-90-5	ethylene dimethacrylate				
	oral	LD50 8700 mg/kg	Rat	ECHA Dossier	FDA (1959)

Irritation and corrosivity

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 8 of 13

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

rabbit, not irritating - slightly irritating. If contact with skin is prolonged and/or frequent, irritations cannot be excluded. Skin irritant Category 2 (UN-GHS).

Sensitising effects

May cause an allergic skin reaction. (methyl methacrylate; 1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate; ethylene dimethacrylate)

Respiratory or skin sensitisation mouse, LLNA (Local Lymph Node Assay), (own study): sensitizing. man, In humans various types of allergic reactions have been observed (symptoms: headache, eye irritations, skin affections). Skin Sensitisation Category 1B (UN-GHS) People who suffer from skin sensitization problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this mixture.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Mutagenicity assessment: Positive as well as negative results in in vitro mutagenicity/ genotoxicity tests. No experimental indication of genotoxicity in vivo available. In summary not mutagenic according to internationally accepted criteria.

STOT-single exposure

May cause respiratory irritation. (methyl methacrylate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure: (structure-activity-relationships)

Aspiration hazard

Based on available data, the classification criteria are not met.
no evidence for hazardous properties.

Specific effects in experiment on an animal

There are no data available on the mixture itself.

Additional information on tests

The mixture is classified as hazardous according to Directive 1999/45/EC.

Practical experience

May cause an allergic skin reaction. May produce an allergic reaction.

11.2. Information on other hazards**Further information**

Repeated exposure may cause skin dryness or cracking. Frequently or prolonged contact with skin may cause dermal irritation. Do not breathe gas/vapour/aerosol.

SECTION 12: Ecological information**12.1. Toxicity**

Conclusive data but not sufficient for classification

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 9 of 13

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
80-62-6	methyl methacrylate					
	Acute fish toxicity	LC50 191 mg/l	96 h	Lepomis macrochirus (Bluegill)	Merck	
	Acute algae toxicity	ErC50 > 110 mg/l	72 h	Pseudokirchneriella subcapitata	REACH Dossier	OECD 201
	Acute crustacea toxicity	EC50 69 mg/l	48 h	Daphnia magna (Big water flea)	REACH Dossier	EPA OTS 797.1300
2082-81-7	1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate					
	Acute fish toxicity	LC50 5,861 mg/l	96 h	Pimephales promelas (fathead minnow)	EpiSuite QSAR tool	Quantitative structure-activity relationship (QSAR)

12.2. Persistence and degradability

Readily biodegradable (according to OECD criteria). Photo-chemical elimination

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
80-62-6	methyl methacrylate			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	94 %	14	Publication
	Readily biodegradable (according to OECD criteria).			
	EPA, title 40 Code of Federal Regulations Part 160	> 99 %	2	40 CFR 160
	Readily biodegradable (according to OECD criteria).			
2082-81-7	1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate			
	OECD 310 (Headspace Test)	76 - 92 %	28	REACH Dossier
	Biodegradable.			
97-90-5	ethylene dimethacrylate			
	OECD 301 F, GLP	69 %	28	ECHA Dossier
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
80-62-6	methyl methacrylate	1,38
2082-81-7	1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate	3,1
97-90-5	ethylene dimethacrylate	2,4

BCF

CAS No	Chemical name	BCF	Species	Source
80-62-6	methyl methacrylate	2,97 - 3,5	Pisces	SDB HIT-ICE, B
2082-81-7	1,4-butandiol dimethacrylate, Tetramethylene dimethacrylate	59,21	n/h	EpiSuite QSAR tool
97-90-5	ethylene dimethacrylate	13,32	n.n.	EPIWIN Tool

12.4. Mobility in soil

The product has not been tested. On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment cannot be ruled out. If product enters soil, it will be mobile and may contaminate groundwater.

12.5. Results of PBT and vPvB assessment

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 10 of 13

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

There are no data available on the preparation/mixture itself.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - used product

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

List of Wastes Code - contaminated packaging

070208 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of plastics, synthetic rubber and man-made fibres; other still bottoms and reaction residues; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Contaminated packages must be completely emptied and can be re-used following proper cleaning.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:

UN 1247

14.2. UN proper shipping name:

METHYL METHACRYLATE MONOMER, STABILIZED

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

386

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

339

Tunnel restriction code:

D/E

Other applicable information (land transport)

E2

Inland waterways transport (ADN)

14.1. UN number or ID number:

UN 1247

Safety Data Sheet

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 11 of 13

14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 386
Limited quantity: 1 L
Excepted quantity: E2

Other applicable information (inland waterways transport)
E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: 386
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Other applicable information (marine transport)
E2

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1247
14.2. UN proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A209
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

Passenger-LQ: Y341
E2

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No
Danger releasing substance: See section 14.2.

**Safety Data Sheet**

according to UK REACH Regulation

Revision date: 13.07.2023

artDentine PLUS Liquid LT

Product code: artConceptPLUSLT

Page 12 of 13

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

Other applicable information

The substance evaporates gradually into the atmosphere from the surface of the

Further information Do not packing together with acrylate polymer powder!

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Information according to 2012/18/EU
(SEVESO III):

P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D):

2 - obviously hazardous to water

Skin resorption/Sensitization:

Causes allergic hypersensitivity reactions.

Biocide registry number:

not applicable

Additional information

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

:
:**15.2. Chemical safety assessment**

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s):

1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Key literature references and sources for data

OECD-SIDS

ECHA - REACH Dossier

TOXNET - Hazardous Substances Data Bank (HSDAB) & ChemIDplus

**Safety Data Sheet**

according to UK REACH Regulation

artDentine PLUS Liquid LT

Revision date: 13.07.2023

Product code: artConceptPLUSLT

Page 13 of 13

Environmental Protection Agency (EPA) - Chemistry Dashboard

EpiSuite - QSAR tool

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Skin Irrit. 2; H315	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)